VAN CUTSEM tools
Quality tools for metalworking

KMO-zone Doornpark 19 – 9120 BEVEREN-WAAS - BELGIUM
tel +32 (0)3 776 84 92 - info@vancutsemtools.be - www.vancutsemtools.be

Topkwaliteit aan een lage snijkost!

TOROMILL X2



Palbit profielfrees 35190

- Profielfrees met robuuste dubbelzijdige freesplaten:
- RNHX1204 freesplaten: **12 snijkanten** - max.Ap: 3,0mm
- Toepassingsgebied: P M K S
- Levertijd: 24/48h

- 12-snijkanten = kostenefficiënt frezen!
- Hoog verspaningsvolume.

Opgelet:
Prijstijging: 2,5%
(vanaf 01/01/2025)

Palbit prijzen ... (prijzen zijn geldig tot de jaarlijkse Palbit prijswijzigingen)

Bij afname van:	Universele 12-snijkanten freesplaat (max Ap: 3,0mm)		€/snijpl. *bruto*	korting	€/snijpl. *netto*	€/snijkant *netto*
10 stks	RNHX 1204 MOE-LP PHP 930	P	19,08 €	-20%	15,26 €	1,27 €
≥ 30 stks	RNHX 1204 MOE-LP PHP 930	P	19,08 €	-35%	12,40 €	1,03 €
10 stks	RNHX 1204 MOE-LP PHH 530	M S	23,85 €	-20%	19,08 €	1,59 €
≥ 30 stks	RNHX 1204 MOE-LP PHH 530	M S	23,85 €	-35%	15,50 €	1,29 €

Opgelet:
Prijstijging: 2,5%
(vanaf 01/01/2025)


Palbit freeslichamen 35190

D_c		Inhoud	Set €
40	4	040A35190-04-07-016040	238,44 €
50	5	050A35190-05-07-022040	305,09 €
63	6	063A35190-06-07-022050	338,31 €
80	7	080A35190-07-07-027050	371,54 €
100	9	100A35190-09-07-032050	424,09 €

VAN CUTSEM tools
Quality tools for metalworking

palbit
TOOLING SOLUTIONS EXPERTS
SINCE1916

Double-sided
round milling insert




TOROMILL X2
35190

Text




PDF

INSERT SIZE 12 RNHX 1204



SINCE 1916






Arbor Mounting

γ_p=-7°

Order code Código	Reference Referência Referencia		Dimensions | Dimensões | Dimensiones (mm)					Kg	Specifications		Insert Pastilha Inserto	Stock
			ØDc	ØDc2	Ød	Ødg	L		Arbor Type	Ap max (mm)		
181111600	040A35190-04-07-016040	4	40	32	16	32	40	0,20	A	3,0	RNHX 1204 M0E...	◈
181100200	050A35190-05-07-022040	5	50	42	22	40	40	0,24	A	3,0	RNHX 1204 M0E...	◈
181128800	063A35190-06-07-022050	6	63	49	22	48	50	0,55	A	3,0	RNHX 1204 M0E...	◈
181128900	080A35190-07-07-027050	7	80	60	27	60	50	0,78	A	3,0	RNHX 1204 M0E...	◈
181175600	100A35190-09-07-032050	9	100	80	32	70	50	1,00	B	3,0	RNHX 1204 M0E...	◈

◈ Stock item | Produto de stock | Itens de stock ◯ Available under request (see page A-8) | Disponível sobre consulta (consulte a página A-8) | Disponible bajo consulta (mire pagina A-8)






Threaded Coupling

γ_p=-7°

Order code Código	Reference Referência Referencia		Dimensions | Dimensões | Dimensiones (mm)				Kg	Specifications	Insert Pastilha Inserto	Stock
			ØDc	ØM	Ødg	L		Ap max (mm)		
181128500	032R35190-03-07-M16040	3	32	M16	29	40	0,16	3,0	RNHX 1204 M0E...	◯
181128700	042R35190-04-07-M16040	4	42	M16	29	40	0,20	3,0	RNHX 1204 M0E...	◯

◈ Stock item | Produto de stock | Itens de stock ◯ Available under request (see page A-8) | Disponível sobre consulta (consulte a página A-8) | Disponible bajo consulta (mire pagina A-8)


TOROMILL X2 35190
RNHX





Weldon Shank

γ_p=-7°




Order code Código	Reference Referência Referencia		Dimensions | Dimensões | Dimensiones (mm)				Kg	Specifications	Insert Pastilha Inserto	Stock
			ØDc	Ød/M	L	L1		Ap max (mm)		
181087000	032W35190-03-07-032125	3	32	32	125	42	0,98	3,0	RNHX 1204 M0E...	◎

◎ Stock item | Produto de stock | Itens de stock ○ Available under request (see page A-9) | Disponível sobre consulta (consulte a página A-9) | Disponible bajo consulta (mire pagina A-9)

RNHX 1204... | Inserts | Pastilhas | Plaquitas


RNHX-LP



RNHX-MP



RNHX-LP | MP



		P			M			K		S		Dimensions Dimensões Dimensiones (mm)	
		PVD			PVD			PVD		PVD			
	(2) Grade code	T1	P4	Z2	X9	Z2	Z3	T1	P4	X9	Z3		
(1) Geometry code	ISO Reference	PHP920	PHP930	PHP530	PHH930	PHP530	PHH530	PHP920	PHP930	PHH930	PHH530	IC	S
1112030	RNHX 1204 M0E-LP	◎		◎	◎	◎	◎			◎	◎	12,00	4,76
1112052	RNHX 1204 M0E-MP	◎	◎					◎	◎			12,00	4,76

◎ First choice | Primeira opção | 1ª opción ◎ Stock item | Produto de stock | Itens de stock ○ Available under request (see page A-9) | Disponível sobre consulta (consulte a página A-9) | Disponible bajo consulta (mire pagina A-9)

Insert order code = (1) Geometry Code + (2) Grade Code

palbit TOOLING SOLUTIONS EXPERTS SINCE 1916


TOROMILL X2 35190

SPARE PARTS | Complementos | Repuestos

Order separately

Cutter ØDc	Insert Screw	Key (Torx)	Key (Torx - Nm)	Torque Value
35190	P0401065	XT15	DT1530	3,00

Note: The toolholder is supplied with the XT/PT key. To order the DT key please check the page A-241.
Check the procedures for the clamping screws on the page A-241.



GRADES SELECTION GUIDE | Guia para selecção de graus | Tabla para selección de calidades

ISO	PSM	Material	HB (Brinell)	Grades ← Wear Resistance				Toughness →
				PHP920	PHP930	PHH930	PHP530	PHH530
P	1	Unalloyed Steel	125-220	✓	✓		✓	
	2	Low-Alloyed Steel	220-280	✓	✓		✓	
	3	High-Alloyed Steel	280-380	✓	✓		✓	
M	4	SS - Ferritic / Martensitic	200-330			✓	✓	✓
	5	SS - Austenitic	200-330			✓		✓
	6	SS - Austenitic-ferritic (Duplex)	230-260			✓		✓
K	7	Malleable Cast Iron	130-230	✓	✓			
	8	Grey Cast Iron	180-245	✓	✓			
	9	Nodular Cast iron	160-250	✓	✓			
S	11	Heat Resistant Super Alloys	200-320			✓		✓

Good Conditions Average Conditions Difficult Conditions


RECOMMENDED CUTTING CONDITIONS | Condições de corte recomendadas | Condiciones de corte recomendables

ISO	PSM	Material	HB (Brinell)	Vc (m/min) ← Wear Resistance				Toughness →	RNHX... 12	
				PHP920	PHP930	PHH930	PHP530	PHH530	LP	MP
P	1	Unalloyed Steel	125-220	180-250	160-230	-	180-340	-	0,15-0,45	0,15-0,50
	2	Low-Alloyed Steel	220-280	160-230	140-210	-	180-340	-	0,15-0,45	0,15-0,50
	3	High-Alloyed Steel	280-380	140-220	120-200	-	180-330	-	0,15-0,45	0,15-0,45
M	4	SS - Ferritic / Martensitic	200-330	-	-	140-210	150-270	170-280	0,10-0,35	-
	5	SS - Austenitic	200-330	-	-	120-170	-	160-280	0,10-0,35	-
	6	SS - Austenitic-ferritic (Duplex)	230-260	-	-	100-150	-	150-260	0,10-0,35	-
K	7	Malleable Cast Iron	130-230	-	150-280	-	-	-	-	0,15-0,55
	8	Grey Cast Iron	180-245	-	130-230	-	-	-	-	0,15-0,55
	9	Nodular Cast iron	160-250	-	80-190	-	-	-	-	0,15-0,50
S	11	Heat Resistant Super Alloys	200-320	-	-	30-110	-	30-150	0,05-0,30	-

CHIP-BREAKER SELECTION GUIDE | Guia para aplicações do quebra-aparas | Guía para aplicación del rompevirutas

ISO	PSM	Material	HB (Brinell)	Chip-Breaker Application	
				1st choise	Dificult Operations
P	1	Unalloyed Steel	125-220	LP	MP
	2	Low-Alloyed Steel	220-280	LP	MP
	3	High-Alloyed Steel	280-380	MP	-
M	4	SS - Ferritic / Martensitic	200-330	LP	-
	5	SS - Austenitic	200-330	LP	-
	6	SS - Austenitic-ferritic (Duplex)	230-260	LP	-
K	7	Malleable Cast Iron	130-230	MP	-
	8	Grey Cast Iron	180-245	MP	-
	9	Nodular Cast iron	160-250	MP	-
S	11	Heat Resistant Super Alloys	200-320	LP	-

RAMPING | Descida em rampa | Bajada en rampa



Insert	ØDc	Ramping		
		Max Ramp a°	Max a_p	Min Lr
RNHX 1204	32	1	3	171,9
	40	0,8	3	214,8
	42	0,8	3	214,8
	50	0,8	3	214,8
	63	0,6	3	286,5
	80	0,5	3	343,8

palbit
TOOLING SOLUTIONS EXPERTS
SINCE1916

TOROMILL X2
35190

VAN CUTSEM tools
Quality tools for metalworking

KMO-zone Doornpark 19 – 9120 BEVEREN-WAAS - BELGIUM
tel +32 (0)3 776 84 92 - info@vancutsemtools.be - www.vancutsemtools.be

HEADQUARTERS
PALBIT. S.A.
P.O.Box 4 - Palhal
3854-908 - Branca ALB - Portugal
T (+351) 234 540 300 | F (+351) 234 540 301
palbit@palbit.pt | **www.palbit.pt**

Branch office:
PALBIT México
Emerson 150. Int.803-804. Colonia Chapultepec
Morales Delagación Miguel Hidalgo
C.P. 11570 México DF
T (+52) 5555 454 543 | F (+52) 5552 509 190
info@palbit.com.mx | **www.palbit.com.mx**

SINCE 1916